



## STREAMING's NEW CUTTING EDGE



ES9038PRO  
SABRE DAC

DSD512  
22.6MHz

PCM  
768kHz

USB  
OUTPUT

ALL-NEW  
PSU

OPTICAL  
NETWORK

# LUMIN

# X1

# LUMIN

A NEW STREAMING FLAGSHIP

DUAL ES9038PRO SABRE DAC  
FEATURING 140DB DYNAMIC  
RANGE

DSD512 22.6MHZ


PCM 44.1-768KHZ 16-32-BIT

USB DIGITAL AUDIO OUTPUT

PCM & DSD UPSAMPLING

PSU REDESIGNED INSIDE AND  
OUT WITH NEW  
SINGLE-BILLET CNC CHASSIS

DUAL NETWORK PORTS (ONE  
OPTICAL SFP, ONE RJ45).  
CONNECT ONE TO ROUTER  
AND ONE TO LUMIN L1 OR  
NAS



#### STREAMING PROTOCOL:

UPnP AV protocol with audio streaming extension (OpenHome). Roon Ready. Spotify Connect. TIDAL Connect. Apple AirPlay. Gapless Playback. On-Device Playlist. Multi-Room (Songcast)

#### SUPPORTED AUDIO FILE FORMATS:

DSD :  
DSF (DSD), DFF (DSD), DoP (DSD)  
PCM:  
FLAC, Apple Lossless (ALAC), WAV, AIFF  
OTHER:  
MQA, MP3

#### SUPPORTED SAMPLE RATES & BIT DEPTHS:

PCM, 44.1kHz-768kHz, 16-32-bit, Stereo  
DSD512, 22.6MHz, 1-bit, Stereo

#### Upsampling rates & bit depths:

PCM 384kHz and DSD128 upsampling option for all files up to 192kHz

#### SUPPORTED CONTROL DEVICES:

Apple iOS devices. iOS 5.0 or later required  
Android devices. Android 4.0 (Ice Cream Sandwich) or later required

#### APP FEATURES:

Native support for TIDAL, MQA, Qobuz and TuneIn Radio. Tidal MQA and Qobuz high-res icons to identify high-res music. Multi-room simultaneous playback. Volume control. High-resolution artwork. Artwork caching. Search. Multiple tag handling. Composer tag support. Album-grouping in playlist. Automatic internet links to artists/album/songs. Saving, syncing and restoring of playlists (including Tidal and Qobuz)

#### INPUT:

Gigabit Ethernet Network (1000BASE-T) RJ45  
Gigabit Optical Ethernet (1000BASE-T) SFP  
USB storage, flash drive, USB hard disk (Single-partition FAT32, exFAT and NTFS only)

#### DIGITAL AUDIO OUTPUT:

USB:  
DSD64/128/256/512 2.8-22.6MHz, 1-bit Stereo  
PCM 44.1-768kHz, 16-32-bit Stereo  
COAXIAL BNC:  
PCM 44.1kHz-192kHz, 16-24-bit  
DSD (DoP, DSD over PCM) 2.8MHz, 1-bit

#### POWER SUPPLY:

External dual-toroidal PSU. CNC construction with finish matched to main unit  
Available in 220-240V AC and 110-120V AC versions ~ 50/60Hz

#### FINISH:

Raw brushed aluminium  
Black anodised brushed aluminium

#### OTHER:

LeedH Processing lossless digital volume control  
Programme of Continuous Development - Firmware-upgradable for further features and enhancements

LUMIN: 350mm (W), 345mm (D), 60mm (H), 8kg

PSU: 106mm (W), 334mm (D), 60mm (H), 4kg

WWW.LUMINMUSIC.COM