

MICHI

S430

STEREO POWER AMPLIFIER



2 x 390 Watts of robust power, 4 ohms



Oversized custom-engineered, in-house manufactured toroidal transformer



High-efficiency bulk storage capacitors



Balanced XLR inputs



Includes remote control

The Michi Prestige S430 Stereo Power Amplifier delivers authority, control, and musical refinement expected from the Michi ecosystem. Rated at 230 watts per channel into 8 ohms and 390 watts per channel into 4 ohms, the S430 provides the power and dynamic headroom required to drive high-performance loudspeakers with confidence.

At its heart is a substantial high-current linear power supply built around an oversized, in-house-manufactured toroidal transformer and large reservoir capacitor bank. This foundation supports stable current delivery, firm low-frequency control, expansive soundstaging, and fast, effortless transient response, allowing music to unfold with scale, impact, and natural detail.

Balanced XLR and RCA inputs provide flexible, low-noise connection to premium preamplifiers and source systems, while dual precision 5-way speaker binding posts support secure cable connection and bi-wire speaker configurations. 12V trigger control allows clean integration into complete performance audio systems, including installations built around matching Michi components.

The S430's elegant aluminum chassis, substantial construction, and refined industrial design reflect the engineering discipline beneath the surface. A front-panel TFT display with selectable VU meter and spectrum display views adds visual engagement without distraction. Built as both a precision power amplifier and a natural partner within the Michi Prestige system, the S430 delivers power with poise, refinement, and real musical connection.

MICHI

S430

STEREO POWER AMPLIFIER



SPECIFICATIONS

Power Output (FTC)	250 watts/channel (8 ohms)	General	
Continuous Power Output (Non FTC)	230 watts/channel (8 ohms)	Power Requirements	
Maximum Power Output (Non FTC)	390 watts/channel (4 ohms)	Europe	230 V, 50 Hz
Total Harmonic Distortion	< 0.03%	USA	120 V, 60 Hz
Intermodulation Distortion (60 Hz : 7 kHz, 4:1)	< 0.03%	Power Consumption	550 watts
Frequency Response (0 ± 0.4 dB)	10 Hz-100 kHz	Standby Power Consumption	< 0.5 watts
Damping Factor (1 kHz, 8 ohms)	350	BTU (4 ohms, 1/8th power)	1513 BTU/h
Speaker Impedance	4 ohms minimum	Dimensions (W x H x D)	431 x 148 x 405 mm 17 x 5 5/8 x 16 ins
Signal to Noise Ratio (IHF "A" weighted)	> 115 dB	Front Panel Height	131 mm / 5 1/8 ins
Crosstalk/Separation	> 70 dB	Weight (net)	17.5 kg, 38.6 lbs
Input Sensitivity / Impedance		Finish	Black
Unbalanced	2 V / 12k ohms		
Balanced	4 V / 200k ohms		
Gain			
Unbalanced	26.5 dB		
Balanced	20.5 dB		

All specifications are accurate at the time of printing.
Michi reserves the right to make improvements without notice.

www.michi-hifi.com